Technisches Datenblatt

LED-Leiste mit Netzteil für **Paro**

Basisset schwarz 1x 0,5 m / 1,0 m / 1,5 m LED-Leiste mit Netzteil

Allgemeine Daten	
Austauschbares Leuchtmittel	Durch den Hersteller oder eine Fachkraft
Lebensdauer	50.000 h
Schaltzyklen bis zum Ausfall	> 20.000
Schutzart	IP20
Max. Betriebstemperatur bei 25°C Umgebungstemperatur	40° C
Befestigung	Kleben/Klemmen
Stecker	Eurostecker
Schutzklasse	Schutzklasse II
Maximale Anzahl in Reihe geschalteter Leuchtmittel	6 Stück
Elektrische Daten	Leistung 30 W
Netzteil, Schutzklasse II	230 Vac Voltage 50/60 Hz
Leuchten, Schutzklasse III	24 Vdc
Leistungsfaktor	≥ 0,9
Zulässige Last am Netzteil	Maximal 30 W
Ausgangsspannung	24 Vdc

Schutzklasse II ⧈. Diese Leuchte ist besonders isoliert und darf nicht an einen Schutzleiter angeschlossen werden.

Schutzklasse II. Bezieht sich nur auf das Netzteil.
Schutzklasse III bezieht sich auf den Teil der Leuchte.



Lichttechnische Daten	
Angabe zur Lichtquelle	125 lm pro 0,5 m Modul
Lichtfarbe	warmweiss
Farbtemperatur	2.700 K
Farbwiedergabeindex	> 90
Standardabweichung des Farbabgleichs	3 sdcm
Abstrahlwinkel	180°
Zündzeit	< 0,5 Sekunden
Anlaufzeit	bis 60 % keine
Eingangsspannung und Leistung	24 Vdc, 1,5 W pro 0,5 m Modul

0,5 m LED-Leiste	Enthält 1x Modul
1,0 m LED-Leiste	Enthält 2x Module
1,5 m LED-Leiste	Enthält 3x Module

Das Symbol der durchgestrichenen Mülltonne auf dem Produkt oder der Verpackung bedeutet, dass dieses Produkt nicht mit dem Hausmüll entsorgt werden darf. Das Produkt muss stattdessen am Ende seiner Lebensdauer zu einer Annahmestelle für das Recycling von elektrischen und elektronischen Geräten gebracht werden. Bitte erfragen Sie diese Stelle bei Ihrer zuständigen kommunalen Verwaltung.

Die beiliegende oder einsetzbare LED-Lichtquelle dieser Leuchte darf nur vom Hersteller oder einem von ihm beauftragten Servicetechniker oder einer vergleichbar qualifizierten Person ersetzt werden. Das eingesetzte Betriebsgerät (Trafo, Vorschaltgerät, Ansteuerung etc.) kann durch den Endkunden ausgetauscht werden. Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse „G“, bezogen auf die EU-Verordnung. 2019/2015.

LED Netzteil 24 Vdc 30W 1,25 A Indoor integ. 6-fach Verteiler mini

NT-989052430

Artikelnummer	**Abmessungen**	**Material Gehäuse**	**Farbe**	**Technische Daten**
NT-989052430	180 mm x 52 mm x 16,3 mm	Kunststoff	weiß	Eingangsspannung: 230 Vac Eingangsbereich: 200-240 Vac 50/60 Hz Ausgangsspannung: 24 Vdc stabilisiert Ausgangsstrom: 1,25 A max Leistung: 1-30 W Restwelligkeit: 240 mV Vp-p Gehäusefarbe: weiß Temperaturbereich: -20°C bis +45°C (tc = 75°C)

11/2024

Mit diesen Angaben wollen wir Sie aufgrund unserer Versuche, Erfahrungen, durchgeführte Prüfungen, angewandten Normen, und den Regeln des Fachs nach bestem Gewissen beraten. Unser technischer und kaufmännischer Beratungsdienst steht Ihnen für weitere Auskünfte zur Verfügung. Nehmen Sie bei größeren Bauvorhaben vor Beginn der Bauarbeiten immer den Beratungsdienst in Anspruch. Irrtum und technische Änderung vorbehalten.
W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | 34134 Kassel | info@joka.de | www.joka.de
INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | 2355 Wiener Neudorf | info@inku.at | www.inku.at

Technical data sheet

LED strip with power supply **Paro**

Basic set black 1x 0.5 m / 1.0 m/ 1.5 m LED strip with power supply

General data	
Replaceable light source	By the manufacturer or a specialist
Technical service life	50.000 h
Switching cycles until failure	> 20.000
Type of protection	IP20
Max. Operating temperature at 25°C	40° C
Ambient temperature fastening	Gluing/clamping
Plug	Europlug
Class of protection	Protection Class II
Maximum number of light that can be connected to the power supply	6 pieces
Electrical data	Power 30 W
Operating voltage	230 Vac Voltage, 50/60 Hz
Luminaire protection class III	24 Vdc
Power factor	≥ 0,9
Power output of the ballast	Maximum 30 W
Output voltage	24 Vdc

Protection Class II ⧈. This light is particularly insulated and must not be connected to a protective conductor.

Protection class II. Only refers to the power supply.
Protection class III refers to the part of the light.



Technical lighting data	
Effective luminous flux	125 lm per 0,5 m module
Colour of light	warm-white
Colour temperature	2.700 K
Colour rendering index	> 90
Deviation of the color balance	3 sdcm
Radiation angle	180°
Ignition time	< 0.5 seconds
Warm-up time	up to 60 % none
Input voltage and power	24 Vdc, 1,5 W per 0,5 m module

0,5 m LED-Strip	Contains 1x module
1,0 m LED-Strip	Contains 2x modules
1,5 m LED-Strip	Contains 3x modules

The symbol of the crossed-out garbage can on the product or the packaging means that the product must not be disposed with ordinary household waste. At the end of its useful life, the product must be returned to a point of acceptance for the recycling of electric and electronic device. Please ask your local municipality for the point of acceptance.

The enclosed or usable LED-light source of this lamp may only be replaced by the manufacturer or a service technician commissioned by the manufacturer or a similarly qualified person.The operating device used (transformer, ballast, control, etc.) can be replaced by the end customer. This product contains a light source of energy efficiency class “G”, based on EU - regulation.
2019/2015.

LED power supply 24Vdc 30W 1.25 A Indoor integ. 6-way distributor mini

NT-989052430

Article number	Dimensions	Casing material	Colour	Technical data
NT-989052430	180 mm x 52 mm x 16,3 mm	Plastic material	white	Input voltage: 230 Vac Input range: 200-240 Vac 50/60 Hz Output voltage: 24 Vdc stabilized Output current: 1.25 A max Power: 1-30 W Residual ripple: 240 mV Vp-p Technical housing: white Temperature range: -20°C to +45°C (tc = 75°C)

With this information we want to advise you to the best of our knowledge and based on our tests, experience, tests carried out, standards applied and the rules of the trade. Our technical and commercial advisory service is at your disposal for further information. For larger construction projects, always consult our advisory service before starting construction work. Errors and technical changes excepted.
W. & L. Jordan GmbH | Horst-Dieter-Jordan-Straße 7-10 | 34134 Kassel | info@joka.de | www.joka.de INKU Jordan GmbH & Co. KG | IZ-NÖ Süd | Straße 3 | 2355 Wiener Neudorf | info@inku.at | www.inku.at